

# BONDEX U-26

## superglue



### PRODUCT DESCRIPTION:

Good gap filling capability, slow hardening and high strength. Recommended for rubber, plastic, metal and ceramics.

### PROPERTIES:

Colour: *clear*

Chemical base: *Ethyl*

Max. gap (microns): *10-150*

Viscosity (20°C mPa.s): *300-500*

Adhesion speed: *medium*

Tensile strength DIN 53288 (N/mm<sup>2</sup>): *18-23*

Tensile shear strength DIN 53288 (N/mm<sup>2</sup>): *13-18*

Impact shear strength ASTM D 950 (N.mm/mm<sup>2</sup>): *15-20*

Temperature range: *-50 to +80*

Item no. **926 020** bottle 20 g



Item no. 926 020

Item no.	Contents	Container	Quantity
926 020	20 g	bottle	24 items per box

## NEOVAL OIL

EUROTECH NEOVAL AG | Unterlettenstrasse 14 | CH-9443 Widnau | Tel. +41 71 555 0170 | Fax +41 71 555 0174 | office@eurotech-neoval.ch | UID-NR: CH - 107.781.103 | Migrosbank: IBAN: CH13 0480 1016 1083 6570 8, BIC: MIGRCHZZ80A | PostFinance: IBAN: CH64 0900 000 4002 5174 3, BIC: POFICHBEXXX | [www.eurotech-neoval.ch](http://www.eurotech-neoval.ch)